



LUNEBERG REFLECTORS
MONOSTATIC EQUATORIAL
RECTILINEAR POLARIZATION

Zéphyr

Plan #	4LUN04R0008	
R.C.S. Measurements	<p>We guarantee the specifications of the reflector according to plan # 4LUN04R0008. The reflector is delivered with 3 points of measurement (0° / -15° / +15° of sight at 0° of azimuth). The delivered measurement corresponds to the measurement of the lens alone.</p> <p>Moreover the reflector can be used from S band to Ku band.</p> <p>Further measurement options (patterns, other frequencies...) on specific request.</p>	
Response	<p>Monostatic</p>	
Polarization	<p>Rectilinear. The reflected wave is on the same plane as the wave interrogating the reflector.</p>	
Metallization		<p>Metallization on ± 20° Measurements at ± 15°</p>
Radom	<p>Waterproof composite protection (also against salted ambiance). Acceleration – vibration tests have been passed allowing mounting in supersonic targets</p>	
Specific unit packaging		
<p>⚠ Precautions of use</p>	<p>The response of the lens depends on the environment.</p> <ul style="list-style-type: none"> • Avoid thick fairing • Avoid fairing made of dielectrical material with important losses • Avoid any object (especially metallic) positioned between the lens and the radar (strap, screw...) • Take care in mounting 	



Tect Electronics

The authorized distributor in the Greater China Region





LUNEBERG REFLECTORS
MONOSTATIC EQUATORIAL
RECTILINEAR POLARIZATION

Reference	Frequency range	Measuring frequency (GHz)	Minimum Radar Cross Section guaranteed (sqm)		Diameter of the reflector without fixing		Weight without fixing (kg)
			R.C.S. in the equatorial plane	R.C.S. at $\pm 15^\circ$ of sight	(inches)	(cm)	
XER07	X	9,375	1,0	$\pm 15^\circ$ 0,3	7,0	18	1,3
XER10	X	9,375	6,0	$\pm 15^\circ$ 2,0	10,0	25	3,8
XER12.5	X	9,375	11,0	$\pm 15^\circ$ 8,0	12,5	32	7,4

